

## SV-7065HDUW



The choice for extremely heavy duty conditions, this collision avoidance system supports two cameras and has an extra output for connecting a video recorder or additional monitor. The camera has an ultrawide angle of view providing broader coverage than with standard cameras.

## SPECIFICATIONS

## SV-511 Monitor

|                        |  |
|------------------------|--|
| CRT System             | 5.5-inch   |
| Video System           | NTSC standard signal                                   |
| Horizontal Resolution  | 700 TV lines   |
| Vertical Resolution    | 500 TV lines   |
| Impact Rating          | 6G   |
| Sync System            | Internal   |
| Power Requirement      | 10 ~ 26 VDC  |
| Power Consumption      | 25W  |
| Operating Temperature  | 5°F ~ 140°F (-15°C ~ 60°C)                             |
| Dimensions (w x h x d) | 7.2 in. x 5.4 in. x 7.9 in. (182 mm x 136 mm x 200 mm) |
| Weight                 | 5.3 lbs. (2.4 kg)                                      |

## SV-700HDUW-KIT

|                        |  |
|------------------------|--|
| Image Sensor           | 1/3-inch CCD   |
| Signal Format          | NTSC   |
| Picture Elements       | 270,000 pixels   |
| Angle of View          | 150°   |
| Signal-to-Noise Ratio  | > 44dB (AGC off)   |
| Sync System            | Internal   |
| Horizontal Resolution  | 380 TV lines   |
| Minimum Illumination   | .01 Lux  |
| Impact Rating          | 10G  |
| Power Requirement      | 12 VDC   |
| Operating Temperature  | -22°F ~ 122°F (-30°C ~ 50°C)                             |
| Dimensions (w x h x d) | 4 in. x 1.6 in. x 2.5 in. (101.6 mm x 40.6 mm x 63.5 mm) |
| Weight                 | 1.1 lbs. (0.5 kg)  |

The system activates when you place the vehicle in reverse. With the camera's built-in microphone, people close to the vehicle can communicate directly with you alerting you to possible hazards.

## Features

- The 5.5-inch black and white monitor has two camera inputs with switchable camera views
- A water-resistant housing and an 8 mm polyurethane cable with a pigtail connector provides a watertight connection protecting the camera from moisture
- The camera has a 150° angle of view for broad viewing coverage, and an integrated auto iris and infrared illuminators for better image quality in bright or low light conditions

## Optional Accessories



### LCD RAM Mount and Swivel Pedestal

Safety Vision offers a variety of mounting options for our monitors. The ram mount is ideal for heavy duty operations and the swivel pedestal allows for flexible viewing angles.



### Camera Cables and Cages

Safety Vision offers a wide range of cable types and lengths from 16 feet to over 100 feet. Sectional cables provide ease of installation and repair. Heavy duty operations benefit from the addition of camera cages for enhanced camera protection.

## Warranty Agreement

Safety Vision's standard warranty for new items is one year. Extended warranties and advance replacement agreements also are available: Ask your sales or customer service representative for details.

### CORPORATE HEADQUARTERS

6100 W. Sam Houston Pkwy. N.  
Houston, TX 77041-5113  
Main: 713.896.6600  
Toll Free: 800.880.8855  
Fax: 713.896.6640

[www.safetyvision.com](http://www.safetyvision.com)

# SAFETY VISION®

*Mobile video solutions for enhanced safety*