

GEN 2 HIGH DEFINITION IP CAMERA



The Gen 2 series of High Definition IP cameras are compact, rugged and designed to withstand the harsh shock and vibration of mobile vehicle environments. The powerful processing architecture enables seamless networking, superior low light performance and dual streaming capabilities utilizing the latest H.264 compression schemes. Available as indoor and IP67 rated outdoor models, the Gen 2 series is easy to install utilizing a single cable, Power over Ethernet (PoE) connection and can be tailored with custom enclosure colors to seamlessly blend with vehicle aesthetics.

| SPECIFICATIONS | |
|--|--|
| PART NO. 60-200000 (INTERIOR) and 60-300000 (EXTERIOR) | |
| Image Sensor | 1/2.7 inch Progressive CMOS |
| Effective Pixels | 1920(H) x 1080(V) |
| Lens Focal Length | 4 mm, F1.5 2.8 mm, F2.0 |
| Field of View | 78° horizontal, 45° vertical 110° horizontal, 81.5° vertical |
| Minimum Illumination | 0.1 Lux |
| Day/Night Function | IR Cut Filter |
| Shutter Speed | 1 – 1/10,000 sec. |
| White Balance | Manual/AWB/ATW |
| Compression | Video: H.264/MJPEG Audio: G.711/G.726 |
| Supported Resolutions | Full HD 1080p/SXGA/HD 720p/XGA/SVGA/D1/VGA/CIF |
| Image Settings | Brightness, Exposure, Sharpness, Contrast, White Balance, Saturation, Backlight Compensation |
| Custom Settings | Motion Detection, Privacy Mask, Tampering Alarm |
| Interface | 10/100Mbps Ethernet (RJ-45) |
| Protocols | IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF |
| Security | HTTPS, IP Filter, IEEE 802.1X |
| Internet Browser | Internet Explorer (6.0+), Chrome, Firefox, Safari |
| Connectors | RJ-45, microSDHC 32GB support |
| Power Source | Power over Ethernet (PoE) |
| Power Consumption | 3.5W |
| Operating Temperature | 14°F ~ 122°F (-10°C ~ 50°C) |
| Environmental | IP67 (exterior only) |
| Dimensions | 4.3 in dia. x 1.9 in (110.2 mm dia. x 47.7 mm) |
| Weight | 0.4 lbs (180g) |

*Simulated screenshot

POWERFUL IMAGING

The Gen 2 series of IP cameras support H.264 and MJPEG compression with dual streaming capability. Streams can be configured to support resolutions ranging from CIF up to high definition 1080P to maximize recording times while capturing event videos at resolutions up to 9x greater than analog cameras. Finally, the Gen 2 series utilizes industry leading progressive scan image sensors with outstanding dynamic range and low light capabilities to provide crisp, clear, evidentiary video in the most challenging lighting conditions.

RUGGED AESTHETICS

The Gen 2 series come standard with rugged, low profile, polycarbonate domes and are available with indoor and outdoor rated enclosures rated to IP67. The vandal resistant cameras come standard with software based tamper alarm and are designed to eliminate exposed wiring and minimize surface area. The low profile enclosures can be further customized with color schemes to seamlessly blend with vehicle interiors and exteriors.

FLEXIBLE NETWORKING

The Gen 2 series is designed for plug and play operation with the Safety Vision RoadRecorder® 7000 network video recorder. Using Power over Ethernet (PoE) cabling, the units are automatically powered and configured by the RoadRecorder® 7000 and require no additional programming. Additional features such as digital zoom, image flip, privacy masks, contrast, white balance, LED notification, motion detection, microSD recording and audio can be customized by authorized users directly through the built in web server of the Gen 2.

Please discuss our installation, training, extended warranty, spare-in-the-air, and onsite service options with your mobile video solutions specialist!